

Applications

- Marine Science
- Manned Submersibles
- HD Inspection and Survey
- Observation and Situational Awareness
- Vessel Hull Mount

OE14-522HDIP



High Definition, Ethernet, Pan & Tilt, Zoom, Camera

- 1080p / 720p / NTSC / PAL 10:1
- Zoom Lens
- 230° Optical Viewing
- Low latency streaming <150ms

The OE14-522 high definition, ethernet, pan & tilt zoom camera has been designed for use in subsea environment and is ideal suited to HD inspection & survey tasks, general observation & situational awareness tasks, marine science, (HOV) manned submersible deployment and vessel hull mount (research vessel and mega yacht) applications.


The OE14-522 high definition, ethernet, pan & tilt zoom camera is packaged within a robust 4500msw depth rated titanium alloy housing and features a unique gimbal head design, providing 230° angular coverage on the pan axis and 224° angular coverage on the tilt axis.

The camera benefits from a custom engineered optical arrangement ensuring the image remains in focus through the complete range of movement on both axes. With a 10:1 optical zoom lens the OE14-522 will focus from as close as 10mm from the front port to infinity, making it the perfect choice for both close up and stand-off inspections.

The OE14-522 high definition, ethernet camera has been designed using the latest imaging technology and features a 1/3" CMOS type progressive scan sensor. The camera can produce up to four, H.264/ MPEG-4 compressed, RTSP and MPEG-TS compliant video streams.

Camera functions can be controlled through Imenco's GUI (Graphical User Interface) or by proprietary command protocol transmitted in HTTP format over a 10/100 Base-Tx Fast Ethernet Network connection. An optional flange mount housing assembly is also available for integration into research vessels and mega yacht hulls.

For further information, email
camera.sales.uk@imenco.com



Applications

- Marine Science
- Manned Submersibles
- HD Inspection and Survey
- Observation and Situational Awareness
- Vessel Hull Mount

OE14-522HDIP

Technical Specifications

Performance & Electrical	
Horizontal Resolution	800 TVL/PH
Light Sensitivity	350mV video at 0.5 lux faceplate (1/30 sec, F1.8)
Minimum Scene Illumination	2 lux
Signal to Noise Ratio	>48dB (weighted)
Sensor	1/3" Type Progressive Scan CMOS
Power Input	16 - 24 VDC, 1A (max)
Video & Network	
Sensor Resolution	1920 (H) x 1080 (V) active pixels
Scan Standards	1080p/720p,50fps 1080p/720p,59.94fps PAL/NTSC VBS Composite video
Video Compression	H.264 and Motion JPEG
Video Streaming	Up to 4 simultaneous streams
Interface	10/100 Base TX Ethernet
Protocols	IPv4, TCP/IP, UDP, IGMP (Multicast), HTTP, RTSP, DNS
Latency	< 150ms*
Optical	
Lens	5.1mm to 51mm, 10:1 optical zoom, F1.8
AOV in water	Horizontal: 45° (wide) Vertical: 29° (wide) Diagonal: 50.5° (wide)
Iris Control	Automatic (manual control available through GUI)
Focus Range	10mm to infinity (at wide angle) 1000mm to infinity (at tele angle)
Angular Coverage	
Pan & Tilt	Pan: ±100°, Tilt: ±100° (with lens at wide angle setting)
Pan & Tilt, Zoom and Focus Control	GUI or optional joystick terminal
Mechanical	
Dimensions	Diameter: 140mm (Main Body), 170mm (Dome) Length: 232mm (excl. connector)
Weight	In air: 6.5 Kg, In water: 2.7 Kg (shipping weight 14.6kg)
Housing Material	Titanium alloy 6AL/4V ASTM B3 48
Connector	Configuration dependant
Environmental	
Operating Depth	4500 msw (other depth rated housing options are available)
Temperature	Operating: -5 to 40°C, Storage: -20 to 60°C
Shock	30G peak acceleration, 25ms half sine duration, on all three axes
Vibration	10G, from 20 to 150HZ on all three axes
Electromagnetic Compatibility	BS EN 61000-6-3: 2007 Emission and BS EN 61000-6-1: 2007 Immunity

oe14522HDIP_Datasheet_Rev.E

* When Tested with Imenco Subvis Smartview Media Player

